




Europäisches Patentamt
European Patent Office
Office européen des brevets



Publication number : **0 442 727 A2**

⑫

EUROPEAN PATENT APPLICATION

⑪ Application number : 91301173.0

⑤ Int. Cl.⁵ : G01B 7/06

⑫ Date of filing : 13.02.91

⑩ Priority : 14.02.90 JP 13276/90
16.02.90 JP 35571/90

⑬ Date of publication of application :
21.08.91 Bulletin 91/34

⑭ Designated Contracting States :
DE GB IT

⑮ Applicant : MURATA MANUFACTURING CO.,
LTD.
2-26-10, Tenjin
Nagaokakyo-shi Kyoto (JP)

⑯ Inventor : Masuda, Noboru
1-17-18, Nishlaoki
Kawaguchi-shi, Saitama (JP)
Inventor : Oosawa, Tetsuo
5-2-2-1219, Ohji, Kita-ku
Tokyo (JP)
Inventor : Fujii, Yasutaka
7-11-5, Seishin
Sagamihara-shi, Kanagawa (JP)

⑰ Representative : Lawrence, John Gordon et al
McNeight & Lawrence Regent House Heaton
Lane
Stockport, Cheshire SK4 1BS (GB)

② Paper thickness detecting apparatus.

③ There is disclosed a paper thickness detecting apparatus comprising :
an electrode detecting unit constituted by a ground electrode and a detecting electrode arranged in upper and lower positions of a running path of paper to oppose each other ;
an oscillating circuit for generating an oscillation frequency signal ;
a resonant circuit for shifting a resonance point in response to a change in electrostatic capacitance corresponding to a change in paper thickness detected by said electrode detecting unit, and
a detecting circuit for detecting an output of said resonant circuit.

EP 0 442 727 A2

fore, information indicating, e.g. a paper thickness, overlapping of sheets of paper, a paper length, or a deviation between overlapped sheets of paper can be detected with high sensitivity, high precision, and high reliability, resulting in a very large technical value.

Claims

1. A paper thickness detecting apparatus comprising :

an electrode detecting unit constituted by a ground electrode and a detecting electrode arranged in upper and lower positions of a running path of paper to oppose each other ;

an oscillating circuit for generating an oscillation frequency signal ;

a resonant circuit for shifting a resonance point in response to a change in electrostatic capacitance corresponding to a change in paper thickness detected by said electrode detecting unit, and

a detecting circuit for detecting an output of said resonant circuit.

2. A paper thickness detecting apparatus according to claim 1 wherein a high-impedance converting circuit is connected between said oscillating circuit unit and said tuning circuit.

3. A paper thickness detecting apparatus according to claim 1 further comprising an amplifying circuit for amplifying an output of said detecting circuit.

4. A paper thickness detecting apparatus according to claim 3 further comprising an AFC circuit for controlling gain of the output of said amplifying circuit.

5. A paper thickness detecting apparatus according to claim 1 wherein both said oscillating circuit and said tuning circuit include ceramic resonators.

6. A paper thickness detecting apparatus according to claim 1 wherein said oscillating circuit comprises an oscillating circuit unit and a high-impedance converting circuit.

7. A paper thickness detecting apparatus according to claim 1 wherein said detecting circuit comprises a high-impedance circuit and a signal detecting circuit for envelope-detecting an output signal from said resonant circuit.

8. A paper thickness detecting apparatus comprising :

a detecting unit including first and second detecting electrodes arranged along a running

path of paper ;

a signal oscillating circuit for generating an oscillation frequency signal ;

a first sensor circuit for shifting resonance point in response to a change in electrostatic capacitance detected by said first electrode detecting unit ;

a second sensor circuit for shifting a resonance point in response to a change in electrostatic capacitance detected by said second electrode detecting unit ; and

an output circuit for outputting a signal indicating a difference between the detection signals from said first and second sensor circuits.

9. A paper thickness detecting apparatus according to claim 8 further comprising means for connecting said oscillating circuit and said first and second sensor circuits.

10. A paper thickness detecting apparatus according to claim 8 wherein each of said first and second sensor circuits includes a resonant circuit and a detecting circuit.

11. A paper thickness detecting apparatus according to claim 9 wherein said connecting means is a distributor for distributing said oscillation frequency signal to said first and second circuits.

12. A paper thickness detecting apparatus according to claim 8 wherein said detecting unit comprises said first and second detecting electrodes and a common ground electrode to oppose each other with respect to a passing space of a paper.

13. A paper thickness detecting apparatus according to claim 8 wherein said output circuit comprises a differential amplifier.

14. A paper thickness detecting apparatus according to claim 10 wherein each sensor circuit includes an amplifying circuit for amplifying a signal from said detecting circuit and AFC circuit to prevent a resonance point of said resonant circuit from falling outside a set frequency range.

CONCISE EXPLANATION OF RELEVANCE

EP 0635696 B1 describes a device for the electronic measurement of the thickness of thin webs or sheets, in particular foils, films or paper sheets, consisting of a fixed supporting surface and a tactile sensor arranged in fixed manner and substantially perpendicularly to this supporting surface and having a ferromagnetic tactile member which is movable relative to the supporting surface and, as a function of its position relative to the supporting surface, influences the signal of an inductive transducer in the form of a sensor coil and thus indicates the thickness of the webs or sheets.

